

RIBA Insight Platon Plaster Base - Cavity Drainage Membrane for Plaster Finish

Support information:

- [Frequently asked questions:](#) [How does NBS Plus work?](#) | [How do I comment on my NBS Plus product data?](#) | [What is NBS Create?](#)
- [Quick links:](#) [Home](#) | [My products](#) | [How my products appear in NBS](#) | [How my products appear in NBS Create](#) | [Print this page](#)
- [Resources:](#) [NBS Newsletter, Journal and eNewsletter](#) | [Terms and Conditions](#), [Disclaimer](#) and [Using the NBS Plus logo](#)
- [Contact details:](#) nbsplusproduction@thenbs.com | T: 0845 456 9594

The information below is the NBS Plus product entry for Triton Systems Platon Plaster Base - Cavity Drainage Membrane for Plaster Finish.

Platon Plaster Base - Cavity Drainage Membrane for Plaster Finish

An impermeable high density polyethylene (HDPE) studded membrane. It is impermeable to water, gas and water vapour, and is used on internal walls and vaulted ceilings, above or below ground, in new or existing buildings. It can be used over a contaminated or damp background. The inner surface is finished with a plaster or render coat, or dry lining on plaster dabs.

Fixing to vertical/ sloping surfaces:

Platon Plaster Plugs (8 x 70 mm) at a minimum of 13 per m².

Joint lap:

Minimum two studs overlap is recommended; joints sealed.

More about Platon Plaster Base - Cavity Drainage Membrane for Plaster Finish:

[As standard](#) - [Options](#) - [Approvals](#)



Platon Plaster Base - Cavity Drainage Membrane for Plaster Finish

- Manufacturer: Triton Systems.
 - Web: www.tritonsystems.co.uk.
 - Tel: +44 (0)1322 318830.
 - Product reference: Platon Plaster Base.
- Joint sealant: [\[Not required\]](#).
(AND) [\[Platon Overtape\]](#).
[\[Platon Sealing Rope\]](#).
[\[Platon Sealing Tape\]](#).

Add product

[top](#) ^

Guidance for Platon Plaster Base - Cavity Drainage Membrane for Plaster Finish from Triton Systems

More about Platon Plaster Base - Cavity Drainage Membrane for Plaster Finish: [As standard](#) - [Options](#) - [Approvals](#)

As standard

Colour:

Clear.

Thickness:

- Membrane: 0.5 mm.
- Stud height: 5 mm.

Drainage capacity (maximum):

1.84 L/m².

Options

Joint sealant:

- Platon Overtape: Butyl rubber tape backed with non-woven polypropylene for sealing joints in the membrane; size 115 mm wide x 1 mm thick, roll length 25 m.
- Platon Sealing Rope: Blend of butyl and other rubbers used to seal joints in the membrane, seal the membrane around pipes and openings, and to form a gasket between the mechanical fixings and membrane; size, 10 mm diameter, roll length 5 m; colour, blue.
- Platon Sealing Tape: Butyl rubber tape used to seal joints in the membrane and for use with the 'Wall/ Floor Junction'; size, 30 mm wide x 2 mm thick, roll length 20 m.

Approvals


- British Board of Agrément: 01/3823. 

Further Information

Literature:



[Isola Platon Cavity
Membrane
Installation Manual](#)

 Additional information may be available for [Triton Systems](#) from [ribaproductselector.com](#).

Contacts:

www.tritonsystems.co.uk

technical@tritonsystems.co.uk

T: +44 (0)1322 318830

F: +44 (0)1322 524017

NBS Plus

Triton, NBS Plus Approval Site, 10 August 2012

nbsplusproduction@thenbs.com | T: 0845 456 9594