



TRITON FLEECE BAND

SYNTHETIC REINFORCEMENT BAND

TRITON FLEECE BAND is a synthetic textile reinforcing band which is indispensable for use in details, joints, corners and exceptional situations in liquid waterproofing system.

PROPERTIES

- Great absorption and compatibility with liquid waterproofing systems based on polyurethanes and acrylics.
- Easy applications and adaptable on any surface
- Increases cohesion in Triton TT Vapour Membrane & Triton RC liquid systems.
- Resistant to alkalis in Cement
- Excellent elasticity, which enhances the overall performance of liquid waterproofing systems.
- Complements liquid waterproofing systems as a reinforcement.

PRECAUTIONS

- Do not use Triton FLEECE BAND as a puncture resistant reinforcement where liquid membrane waterproofing is applied. When the liquid membrane system is to be covered with concrete screed, a protective layer such as Platon Double Drain must be placed on the liquid membrane to protect it from puncture.

PACKING

- Bands of 0.3 x 100m (30m²)
- Rolls 1m x 100m (100m²)

APPLICATIONS

- **Triton FLEECE BAND:** Reinforcement for liquid membranes in unique areas such as corners, edges, junctions, bases of roof top equipments, chimneys, etc.
- **Triton FLEECE BAND:** Treatment of cracks in conjunction with the liquid membrane.

TECHNICAL DATA

Composition	Thermal bonded polyester reinforcement fabric /nonwoven
Weight	70 g/m ² UNE – EN ISO 9864
Thickness	0.65 mm UNE – EN ISO 9863 – 1
Tensile Strength	1.8 KN/m (Long) 4.2 KN/m (Transv.) UNE – EN ISO 10319
Elongation	Long: 93%, Transv: 94%
Static indentation	500 N (0.5 KN) CBR UNE – EN ISO 12236

For further information contact:

Triton Chemical Manufacturing Co. Ltd. T/a Triton Systems

Units 3 –5 Crayford Commercial Centre
Greyhound Way, Crayford, Kent DA1 4HF
Tel: 01322 318830 Fax: 01322 524017

www.tritonsystems.co.uk
info@tritonsystems.co.uk