



**Triton Systems** 

Units 3-5 Crayford Commercial Centre, Greyhound Way Crayford, Kent DA1 4HF

Tel: 01322 318830 Fax: 01322 524017

www.tritonsystems.co.uk

info@tritonsystems.co.uk

Publication date

Revision date 20/01/2019

MSDS Ref: TR 205

07/06/2004

TRIPROOF AQ

1. PRODUCT NAME:

Emergency Telephone Number: 01322 318830 Hours of Operation: 9.00am-17.00pm Mon-Fri

2. HAZARD IDENTIFICATION

According to regulation (EC) No 1271/2008

(CLP)

No particular hazards known.

3. COMPOSITION

Emulsion of silane / siloxanes.

4. FIRST AID

AFTER INHALATION: Ensure supply of fresh air.

AFTER CONTACT WITH SKIN In case of contact with skin wash off with soap and water.

AFTER CONTACT WITH EYES: Flush eyes immediately and thoroughly with plenty of clean water.

AFTER INGESTION: Call for medical advice immediately, show the container or label.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Foam, Carbon dioxide, dry powder, water spray.

SPECIAL HAZARDS FROM THE SUBSTANCE ITSELF, ITS COMBUSTIOPN PRODUCTS OR

FROM ITS VAPOURS

In the event of a fire the following can be released: Carbon Monoxide,

Carbon Dioxide, Silicon Dioxide.

SPECIAL PROTECTIVE EQUIPMENT FOR

FIREFIGHTERS:

Do not inhale explosion and / or combustion gases.

#### 6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS: Keep away from sources of ignition.

Use personal protective equipment.

**ENVIRONMENTAL PRECAUTIONS:** Do not allow to enter drains or waterways. Do not discharge into the

subsoil/soil.

METHODS FOR CLEANING UP/TAKING UP Take up with absorbent material (e.g. sand, kieselguhr, universal

Dispose of absorbed material in accordance with local regulations.



### 7. HANDLING AND STORAGE

**HANDLING** 

ADVICE ON PROTECTION AGAINST FIRE Keep away from sources of ignition – No Smoking. Vapours may form

explosive mixtures with air. Cool endangered containers by water

spray.

**STORAGE** 

FURTHER INFORMATION Keep container tightly closed.

STORAGE STABILITY

OTHER DATA Storage period up to 6 months.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

PERSONAL PROTECTION EQUIPMENT

HYGIENE MEASURES Wash hands before breaks and after work.

RESPIRATORY PROTECTON in case of formation of vapours / aerosol: short term; filter mask, filter

A-P2

HAND PROTECTION PVC gloves

EYE PROTECTION Goggles with side pieces

SKIN AND BODY PROTECTION Light protective clothing.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Milk white Liquid
Odour	Slight, typical
рН	7-8 at 25°C (as supplied)
Boiling Point	Approx 100°C
Melting Point	-
Flash Point	>100°C
Flammability / autoflammability	Not Relevant
Explosive Properties:	No explosive

Oxidising Properties	None
Vapour Pressure	Not relevant
Relative density	Approx 1g/cm³ at 25°C
Bulk density	•
Viscosity	•
Solubility	Miscible
Partition Coefficient	No data
Other data	

### 10. STABILITY / REACTIVITY

THERMAL DECOMPOSITION: Not measured

HAZARDOUS REACTIONS: No hazardous reactions with proper storage and handling.

HAZARDOUS DECOMPOSITION: If left standing for a long time, alcohol may build up by hydrolysis.

# 11. TOXICOLOGICAL INFORMATION

NOTE: Proper use provided, no adverse health effects have been observed or become known to us.

# 12. ECOLOGICAL INFORMATION

The product is considered to be a weak water pollutant. Do not allow to enter soil, waterways or ditches.

# **Safety Data Sheet**



### 13. DISPOSAL CONSIDERATIONS

DISPOSAL OF PRODUCT: In accordance with local authority regulations, take to special waste

incineration plant.

CONTAMINATED PACKAGING: Uncleaned packaging should be treated as for the product. If

thoroughly rinsed, it may be treated as general waste for incineration,

landfill or recycling, according to the regulations.

### 14. TRANSPORT INFORMATION

Not regulated for Land, Inland waterways, Sea or Air transport.

#### 15. REGULATORY INFORMATION

CLASSIFICATION Not classified.

No hazard warning label required.

### 16. OTHER INFORMATION

For use, after dilution with water as a masonry water repellent.

The information contained in this data sheet is to the best of our knowledge accurate at the date of publication, but we cannot accept responsibility that it is sufficient or correct in all cases.

The data contained herein does not constitute a specification. Such information is available from the technical data sheet for the product.

Abbreviations: OES – occupational exposure standard. STEL – short-term exposure limit. LTEL – long term exposure limit. TWA – time weighted (8 hour) average. LEL – lower explosive limit. UEL – upper explosive limit.