



## Triton TWS-EX Primer

Triton TWS-EX Primer is designed to be used in conjunction with Triton TWS-EX100 and Triton TWS-EX100GM membranes in order to consolidate the substrate and ensure complete bond development.

Supplied as a single pack, brush applied liquid coating.

Coverage – 8m<sup>2</sup>/L.

### Technical Data

Type	Bitumen solution
Viscosity	500 cP
Solids content	48%
Flash point	>39°C
Wet film thickness	90 – 110 microns
Dry film thickness	45 – 60 microns
Specific gravity	0.92
Packing	Supplied in 5L and 25L drums

## Triton TWS-EX Primer LT (low temperature)

Triton TWS-EX Primer LT is a fast drying primer designed to be used in conjunction with Triton TWS-EX100 and Triton TWS-EX100GM membranes in order to consolidate the substrate and ensure complete bond development.

Classed as moisture tolerant, Triton TWS-EX Primer LT can be applied to damp or slightly green concrete.

Coverage – 8m<sup>2</sup>/L.

Supplied as a single pack, brush applied liquid coating.

### Technical Data

Type	Aromatic solvent/Bitumen solution
Solids content	48%
Specific gravity	0.92
Packing	Supplied in 5L and 25L drums

### Triton Contact Details:

Triton Systems Ltd.  
Units 3 – 5 Crayford Commercial Centre, Greyhound Way, Crayford, Kent DA1 4HF

Tel: 01322 318 830

Fax: 01322 524 017

Email: [info@tritonsystems.co.uk](mailto:info@tritonsystems.co.uk)

[www.tritonsystems.co.uk](http://www.tritonsystems.co.uk)