



Declaration of Performance

Date: 19/10/2018 version 2

Triton TWS-EX100

Product type: Type T

Is in compliance with hEN 13967:2012 and fulfils the testing criteria as per ZA.1 to confirm this compliance.

Description and use: A self-adhesive sheet membrane constructed from an oriented cross laminated high density polyethylene sheeting and a bitumen-polymer adhesive compound. Uses include water proofing foundation, basement, roofs and plaza decks, lift shafts, pits, service reservoir roofs, carpark decks and subways.

Essential characteristics	Performance	Harmonised Technical Specification
Reaction to fire	F	EN 13967 : 2012
Watertightness	Pass	
Durability:		
Watertightness after artificial ageing	Pass	
Watertightness after exposure to chemicals	Pass	
Dangerous substances	NPD	

Certification of the Factory Production Control to attestation level system+2 has been carried out by the notified body:

The British Board of Agrément, Bucknalls Lane, Watford, Herts, WD25 9BA (Notified number 0836)

Factory Control Certificate Number:

0836-CPD-13/F032

Robert Bonnell
Operations Manager

Triton Systems – Crayford, Kent DA1 4HF
(19/10/2018)

Triton Contact Details:

Triton Systems Ltd.
Units 3 – 5 Crayford Commercial Centre, Greyhound Way, Crayford, Kent DA1 4HF

Tel: 01322 318 830
Fax: 01322 524 017
Email: info@tritonsystems.co.uk

www.tritonsystems.co.uk