



Triton WOODZONE DUAL PURPOSE F/I

Description

Triton WOODZONE DUAL PURPOSE F/I is a super concentrate supplied in a plastic container. The special micro-emulsion formulation leads to a better penetration than obtained with the older traditional water based emulsified preservatives. It will provide the necessary control & long term protection of wood against wood boring insects & wood destroying fungi (Dry Rot & Wet Rots) for many years thereby giving confidence in any issued long-term guarantee.

Benefits of Woodzone

- Super concentrate (400gms makes 25 Litres)
- Good Penetration
- 1 hour re-entry
- Fully solvent free technology
- No VOC's
- Significant reduction in plastic & paper waste
- Virtually no odour
- Non – flammable

Triton Systems formulations are all cleared under the Government's Pesticide Safety Precaution scheme & under the Control of Pesticide Regulations 1986, for use as directed & carries the **HSE Approval No. 10045**

Typical Applications for Woodzone

- For use on internal & external timbers, fencing & cladding out of ground & surface water contact as a wood preservative against wood boring insects & wood destroying fungi (Dry Rot & Wet Rots)

Bats: The active ingredients have been accepted by the Nature Conservancy bodies as suitable for the treatment of roof voids where bats roost. However, it is a legal requirement to notify the appropriate Nature Conservancy body prior to any treatment of roof spaces where bats have been identified. Treatment must not be carried out whilst bats are at roost (see Safety).

Preparation & Application

Dilute the Triton WOODZONE DUAL PURPOSE F/I 400gm container with 25 litres of water. The diluted product can be applied by brush or spray at the rate of 1 litre of product per 3-4m² of timber surface to refusal. Alternatively, timber may be dipped for a maximum of 3 minutes. Timber to be treated should be reasonably dry before treatment. Any paint varnish or other surface coating should be removed. Any bark should be removed to increase penetration of the treatment.

Coverage

1 litre of diluted product per 3-4m²

Contents

- 3-IODO-2-PROPYNYL-N-BUTYL CARBAMATE – 6.125% w/w
- Propiconazole 18.584% w/w
- Permethrin – 13.02% w/w



Safety

To avoid risks to man & the environment, comply with the instructions for use.

- The COSHH (Control of Substances Hazardous to Health) Regulations 2002 (as amended) apply to use of this product at work
- Avoid excessive contamination of overalls
- Do not contaminate foodstuffs, eating utensils or food contact surfaces.
- This material & its container must be disposed of in a safe way – do not empty into drains – do not contaminate ground, waterbodies or watercourses with chemicals or used containers.
- Avoid contact with skin
- Remove or cover all fish tanks & bowls before application
- Unprotected persons & animals should be kept away from treated areas for 1 hour or until surfaces are dry
- Avoid all contact with plant life
- Cover all storage tanks before application
- All bats are protected under the Wildlife & Countryside Act 1981, before treating any structure used by bats, consult Natural England, Scottish Natural Heritage or the Countryside Council for Wales
- Hazardous to Bees – do not use on beehives or beekeeping equipment
- Wash hands & exposed skin before meals & after use
- If swallowed, seek medical advice immediately & show this container or label

Read the product label and Material Safety Data Sheet (MSDS) for full safety information.

Packaging

400gm in plastic container

Storage

- Keep in a safe place
- Keep out of reach of children
- Keep away from food, drink & animal feeding stuffs
- Should be kept in a cool dry place
- Shelf Life; Concentrate – up to 4 years. Diluted product – up to 6 months.

All products sold by Triton Systems are of high quality. The Company however, cannot govern the conditions of usage & application of its products and any warrant written or implied covers materials only. The information contained in this leaflet is given in good faith but no liability can be assumed by the Company for any damage, loss or injury or patent infringement arising from its use.

For further information please contact:

Triton Chemical Manufacturing Co Ltd T/a Triton Systems

Units 3 – 5 Crayford Commercial Centre, Greyhound Way, Crayford, Kent DA1 4HF

Tel: 01322 318830

Fax: 01322 524017

Email: info@tritonsystems.co.uk

www.tritonsystems.co.uk

Ref: Triton Woodzone Dual Purpose F/I – 11/17