



Triton Bentonite Powder

Description

Triton Bentonite Powder is pulverised Bentonite designed to be used as an accessory to Triton Hydrolock membrane – or used separately as a high grade natural Sodium Bentonite.

Triton Bentonite Powder			
Characteristic	Test Method	Unit	Result
Bentonite (Sodium Bentonite) Bags 20kg			
Montmorillonite Content	CUR 33 (VDG 69)	%	> 75
Swell Index	ASTM D 5890	ml/2g	≥ 24
Fluid Loss	ASTM D 5891	ml	< 18
Moisture Content	DIN 18121-1	%	1 – 6
Water Absorption	DIN 18132	%	> 450
pH 10% Suspension	–	–	9 – 11
Granulation	PN-83/H-10077	mm	0.0 – 1.0

Handling

Triton Bentonite Powder is supplied in bags of 20kg and hence appropriate care and equipment is required for unloading and handling.

Storage

Bags of Triton Bentonite Powder should be stored on stable/level ground with no other material stacked on top. The bags can be stored outdoors when packaged.

Triton Contact Details:

Triton Systems
Units 3 – 5 Crayford Commercial Centre, Greyhound Way, Crayford, Kent DA1 4HF

Tel: 01322 318 830
Fax: 01322 524 017
Email: info@tritonsystems.co.uk

www.tritonsystems.co.uk