



Declaration of Performance

Date: May 2021 version 2

Triton TGS-GM500

Type A in accordance with EN 13967:2012
AVCP System 2+


Triton TGS-GM500 is a sheet membrane designed for use as a damp proof membrane and to prevent the ingress of CO₂ and Radon gas when used in the construction of buildings and dwellings.

Product Name	Colour	Thickness
Triton TGS-GM500	Red	400 micron
Intended use	Designed to be used as a damp proof membrane and to prevent the ingress of ground gas when used in the construction of buildings and dwellings	
Name, registered trade name or registered trade mark and contact address of the supplier	Triton Systems Unit 3 – 5 Crayford Commercial Centre, Greyhound Way, Crayford, Kent DA1 4HF	
System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V	System 2+	
In the case of a declaration of performance concerning a construction product that is covered by a harmonised standard	EN 13967:2017	
Notified body/ies	British Board of Agrément 0836 SGS Italia 1381	

Declaration of performance

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire	F	EN 13967:2017
Water tightness	Pass	
Resistance to impact	≥200mm	
Resistance to static loading	20Kg	
Durability against heat ageing	Pass	
Durability against chemicals	Pass	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the supplier identified above. Signed for and on behalf of the supplier by:

Place	Signature	Date
Crayford, Kent, UK	 Mike Dunn CSSW, CSRT Structural Waterproofing Specialist Triton Systems	20/05/2021

Triton Contact Details:

Triton Systems Ltd.
Units 3 – 5 Crayford Commercial Centre, Greyhound Way, Crayford, Kent DA1 4HF

Tel: 01322 318 830
Fax: 01322 524 017
Email: info@tritonsystems.co.uk

www.tritonsystems.co.uk